



## **Respiratory Protection Program**

### **I. Policy**

California State University, Fullerton (CSUF) intends to maintain, insofar as can reasonably be expected, an environment that will not adversely affect the health, safety and well-being of students, employees, visitors, nor the surrounding community. Because not all working environments can be made completely safe from potentially hazardous substances and atmospheres, CSUF has established the Respiratory Protection Program (RPP) for the safety and well-being of its employees.

### **II. Authority**

California Code of Regulations (CCR), Title 8, § 5144 and Code of Federal Regulations Title 29, Section 1910.134

### **III. Scope**

The Program applies to all University Departments and employees who may work in potentially hazardous atmospheres. It sets forth accepted practices for respiratory equipment users and provides information and guidance for the proper selection, use, and care of the equipment and requirements governing its use. It addresses requirements for protection of the respiratory system from particulate matter, toxic gases, and vapors. It will help safeguard health, as mandatory use of respiratory protective equipment implies that the wearer needs protection from a hazardous atmosphere.

### **IV. Definitions**

Air-Purifying Respirator - A respirator with an air-purifying filter, cartridge, or canister that removes specific air contaminants by passing ambient air through the air-purifying element.

Assigned Protection Factor (APF) - The workplace level of respiratory protection that a respirator or class of respirators is expected to provide to employees when the employer implements a continuing, effective respiratory protection program.

Atmosphere-Supplying Respirator – Respirator that supplies the respirator user with breathing air from a source independent of the ambient atmosphere.

Cartridge - A small container filled with air-purifying media.

Contaminant - A harmful, irritating, or nuisance agent foreign to the normal atmosphere.

Exhalation Valve - A device which allows exhaled air to leave a respirator and prevents infiltration of outside air.

Face-piece - The portion of a respirator that covers the wearer's nose and mouth in a half face-piece and nose, mouth, and eyes in a full face-piece. It seals to the face and includes the headbands, exhalation valve(s), and connections for an air-purifying device.

Filter - A medium used in respirators to remove solid or liquid particles from the air stream entering the respiratory enclosure.

Filtering Face-Piece Respirator - A negative pressure particulate respirator with a filter as an integral part of the face-piece or with the entire face-piece composed of the filtering medium, such as an N95 (e.g. a dust mask).

High-Efficiency Particulate Air (HEPA) Filter - A filter that removes 99.97% of specific particulates from an air stream.

Immediately Dangerous to Life or Health (IDLH) - An atmosphere that poses an immediate threat to life that would cause irreversible adverse health effects, or that would impair a person's ability to escape from a dangerous atmosphere.

Inhalation Valve - A device that allows air to enter the face-piece and prevents exhaled air from leaving the face-piece.

National Institute for Occupational Safety and Health (NIOSH) - A Federal agency that tests, approves, and certifies respirators.

Oxygen Deficient Atmospheres - Air that contains less than 19.5% oxygen by volume.

Powered Air-Purifying Respirator (PAPR) - An air-purifying respirator that uses a blower to force the ambient air through air-purifying elements to the inlet covering.

Particulate - Airborne solid or liquid dusts, fogs, fumes, mists, smokes, or sprays.

Permissible Exposure Limit (PEL) - Contaminant exposure concentrations listed by the California Occupational Health and Safety Administration (Cal/OSHA) that a healthy individual normally can tolerate for 8 hours a day, five days a week, without harmful effects. Particulate concentrations are listed as milligrams per cubic meter of air (mg/m<sup>3</sup>), and gaseous concentrations are listed as parts per million by volume (ppm).

Qualitative Fit Test - A test method that relies on the respirator wearer's sense of taste, smell, or irritation to detect leakage into the respirator facepiece using isoamyl acetate, saccharin, bitrex, or irritant smoke.

Quantitative Fit Test - A test method using a machine to measure the actual amount of leakage into the facepiece that does not rely upon the wearer's sense of taste, smell, or irritation to detect leakage.

Respirator - A device that protects the wearer from inhalation of harmful contaminants.

Self-Contained Breathing Apparatus (SCBA) - An atmosphere-supplying respirator for which the breathing air source is designed to be carried by the user.

Threshold Limit Value (TLV) - Contaminant exposure concentrations published by the American Conference of Governmental Hygienists that a healthy individual normally can tolerate for 8 hours a day, five days a week, and without harmful effects. Particulate concentrations are listed as mg/m<sup>3</sup>, and gaseous concentrations are listed as ppm.

Vapor - The gaseous state of a substance.

## **V. Responsibilities**

### **A. Department**

The Department Chair or Director is responsible for the overall health and safety of employees, visitors, and students at CSUF facilities under their control. They are responsible for assuring the adherence of the mandatory requirements of this program.

### **B. Environmental Health and Safety (EHS)**

1. Reviews and approves purchases of respiratory protection equipment.
2. Provides instruction on the need for respiratory protection and criteria for selection, respirator fitting, use, and maintenance.
3. Coordinates annual medical surveillance for each employee who is required to wear a respirator and maintains authorization records.
4. Conducts annual training for respiratory equipment usage, maintenance, and storage.
5. Conducts annual fit tests and respirator inspections for employees in the Program.
6. Performs exposure assessment and monitoring to determine appropriate respiratory protection requirements.
7. Conducts ongoing evaluations to ensure the written Respiratory Protection Program is being properly implemented, consult employees to ensure they are using respirators properly, assess employee's views on program effectiveness and problems, and make changes to the Program as needed.

### **C. Supervisor**

The employee's immediate supervisor is responsible for:

1. Identifying employees who may need respiratory equipment and contact EHS for assessments and medical exams.
2. Requesting assistance from EHS to evaluate operational changes that may create respiratory hazards.
3. Enforcing the use of respiratory protection equipment and safe work practices when applicable.
4. Ensuring inspections occur prior to use.
5. Confirming that the seal of the face piece is unobstructed by facial hair or other material.

D. Employee

CSUF employees required by the Program to wear respirators are responsible for:

1. Utilizing the issued respiratory protection equipment in accordance with instruction and training provided by EHS.
2. Informing the supervisor of any personal health problems that could be aggravated by the use of respiratory equipment.
3. Guarding against damage and ensuring respirators are not disassembled, modified, or altered in any unauthorized manner.
4. Reporting any observed or suspected malfunctioning respirator to EHS.
5. Using only those brands, sizes, and types of respiratory protection equipment for which they have been trained and fitted.
6. Utilizing proper cartridges for anticipated exposure.
7. Ensuring an effective face piece seal during respirator use.

## VI. Program

A. Authorization

Only staff designated by the supervisor, project leader, or EHS may wear respirators while working at CSUF. Respirator users shall annually complete respirator fit testing, training, and required medical surveillance.

B. Respirator Selection

1. N95 Filtering Facepiece - The N95 filtering face-piece respirators (dust masks) are available to authorized users, such as medical staff at the Student Health

& Counseling Center (SHCC), sworn officers in the CSUF Police Department (CSUF PD), and those who voluntarily choose to use them. The staff at the SHCC and officers at the CSUF PD are fit tested for use in compliance with Title 8, Section 5199, regarding aerosol transmissible diseases. Voluntary users (see section G), having not been identified as having hazardous exposures, and are not fit-tested.

2. Air-purifying Half Face-piece Respirators – These include 3M and North brands, which are available from EHS. They do not provide protection in oxygen deficient atmospheres, but utilize replaceable filter cartridges specific to certain contaminants.
3. Air-purifying Full Face-piece Respirators – These include 3M and North brands. These brands are available from EHS and provide more protection than half-masks because their shape allows a better mask-to-face seal, and they protect the eyes. They utilize the same filtering cartridges as the half face-piece respirators.
4. Full Face-piece Respirators (CSUF PD) – The CSUF Police use specialized masks and filters from Avon and MSA that have been approved by NIOSH as protective against Chemical, Biological, Radiological, Nuclear (CBRN) agents.
5. Filter Cartridges - HEPA filters protect against particulates such as asbestos, lead, and low levels of toxic and radioactive particulates. Other filters protecting against specific contaminants such as acid gases or organic vapors. Combination filters protect against all or a few of these specific contaminants. CSUF Police use special approved filters designed to protect against CBRN agents. Generally, replace the cartridge filters when contaminants are detected through the mask by smell or taste or when breathing becomes difficult. Appendix A provides more specifics on cartridge filters.
6. Powered Air Purifying Respirator (3M Versaflo) – 3M Versaflo Powered Air Purifying Respirator (PAPR) assembly is to be used in asbestos abatement work under 100 square feet, by CSUF's trained asbestos abatement representative. The 3M Versaflo PAPR assembly includes the respiratory helmet, breathing tube, HEPA filter, battery, and charger kit.
7. Atmosphere-Supplying Respirators (SCOTT AIR-PAK 75i SCBA) – To be used in high-hazard atmospheres. High-hazard atmospheres can be encountered during emergency situations, chemical spills, very high concentrations of air contaminants, or the use of materials that have poor warning properties. When there are no reliable data to identify or reasonably estimate exposure levels (e.g. in confined space entries, during emergency procedures, or chemical spills) the atmosphere must be considered IDLH, and atmosphere-supplying respirators must be used.

When an atmosphere-supplying respirator is used, at least one employee will be located outside the unknown or IDLH atmosphere. The standby employee(s) will maintain visual, voice, or signal line communication with the employee(s) in the unknown or IDLH atmosphere and are equipped with SCBA(s) and appropriate retrieval equipment. The standby employee(s) are trained and equipped to provide effective emergency rescue and are required to notify University Police if emergency response is necessary.

Refer to 'Self-Contained Breathing Apparatus (SCBA) Operating Procedures for SCOTT AIR-PAK 75i' for additional use and maintenance procedures.

#### C. Medical Monitoring

Only those individuals medically able to wear respirators and have completed the associated requirements shall be issued a respirator (this includes the N95 masks for SHCC personnel). Those who voluntarily choose to use N95 filtering face-piece respirators as a dust mask are not monitored. Medical monitoring for respirators generally involves a questionnaire consistent with the requirements of Appendix C of CCR Title 8, Section 5144. A contracted occupational health physician reviews it and may request a physical exam based on its answers. For more information on this process, refer to the Medical Monitoring Program.

#### D. Employee Education and Training

Program respirator wearers shall complete training describing available respiratory protective equipment and the care, maintenance, purpose, and function of the equipment. The instruction discusses proper wearing of each respirator, pertinent State and Federal regulations and standards, and CSUF policies. No CSUF employees will be required to work in atmospheres immediately dangerous to life and health, and so the instruction will focus on work in and around low hazard atmospheres and nuisance dusts. Training shall meet the requirements of CCR Title 8, Section 5144.

#### E. Respirator Fit Testing

The Program requires both daily tests and annual quantitative fit tests. EHS inspects respirators during fit tests and offers a quantitative fit test. In addition, respirator wearers shall complete the daily tests prior to use. Archive and current fit test records are maintained by EHS.

##### 1. Daily test

Prior to each use, the respirator wearer will complete a negative pressure test. Don the respirator, and place the hands over the inlet of the filter cartridges to restrict air from passing through; inhale gently so the face-piece slightly collapses; and hold their breath for approximately 10 seconds. If the face-piece remains slightly collapsed and no inward leakage occurs, the test is

successful. Next, complete a positive pressure test by covering the exhalation valve and exhaling gently into the face-piece. If no outward air leakage occurs the test succeeds.

2. Quantitative Test – A machine is used to measure the actual amount of leakage into the face-piece and does not rely upon the wearer’s sense of taste, smell, or irritation in order to detect leakage. The respirator is worn by the wearer and connected to the machine with tubes or hosing. Three methods have been accepted by OSHA: general aerosol, ambient aerosol, and controlled negative pressure.
3. General Information – Fit testing can detect and help correct poorly fitting or performing respirators based upon contaminant leakage into the respirator. During fit tests, adjust the straps properly as comfortably as possible to simulate working conditions. Cal/OSHA lists fit testing procedures in Appendix A of CCR Title 8, Section 5144.

#### F. Assigned Protection Factors

Quantitative tests provide a numerical fit factor for each respirator. These fit factors relate to a specific respirator, but Cal/OSHA has assigned protection factors to different classes of respirators as guidance on proper selection. Like the fit factor, the assigned protection factor (APF) equals the ambient concentration of a contaminant divided by the concentration within the respirator ( $APF = \text{ambient concentration} / \text{inside concentration}$ ). APF generally equals 10 for half face-piece respirators and 50 for full face-piece respirators. Example: Working with a half face-piece respirator in an atmosphere with 10 ppm contaminant concentration equates to an exposure of 1 ppm.

#### G. Voluntary Use

Certain authorized employees may voluntarily use N95 filtering face-piece respirators, available from Material Control or EHS, but may not use half or full face-piece respirators. Voluntary users are exempt from medical monitoring and fit testing, but must read Appendix B to this program.

#### H. Respirator Care

1. Respirators are issued by EHS. Respirator wearers must continually care for their respirators. If a respirator exhibits any defects, return it to EHS and request a new respirator.
2. Inspection – Prior to and after each use the respirator wearer must inspect the following respirator parts to ensure they are not cracked, decomposed, distorted, frayed, loose, pitted, stretched, stiffened, swollen, torn, or warped: rubberized face-piece, plastic adapters, inhalation valves flaps, headband straps, plastic exhalation valve seats, exhalation valve covers, and filter elements.

- a. Self-Contained Breathing Apparatus (SCBA) – Shall be inspected monthly. Air and oxygen cylinders shall be maintained in a fully charged state and shall be recharged when the pressure falls to 90% of the manufacturer's recommended pressure level. The employer shall determine that the regulator and warning devices function properly.
  - i. Certify the respirator by documenting the date the inspection was performed, the name (or signature) of the person who made the inspection, the findings, required remedial action, and a serial number or other means of identifying the inspected respirator; and
  - ii. Provide this information on a tag or label that is attached to the storage compartment for the respirator, is kept with the respirator, or is included in inspection reports stored as paper or electronic files. This information shall be maintained until replaced following a subsequent certification
3. Maintenance – Clean the respirator after use with either respirator wipe pads from EHS and Material Control or by removing the filters and straps and using a mild soap solution and a soft brush. After using soap, rinse with clean, warm water and air dry.
4. Storage – All respirators shall be stored to protect them from damage, contamination, dust, sunlight, extreme temperatures, excessive moisture, and damaging chemicals, and they shall be packed or stored to prevent deformation of the face-piece and exhalation valve.

#### I. Exposure Assessment

Employees wishing to use a respirator should contact EHS for an exposure assessment. EHS will establish whether exposures to hazardous substances exceeds regulatory permissible exposure limits (PEL) or recommended threshold limit values (TLV). The employee enters the Program when exposures exceed the PEL and TLV, and engineering controls and administrative cannot successfully reduce exposures. EHS compares exposures to the respirator APF to select the appropriate respirator.

#### J. Record Keeping

This section requires the employer to establish and retain written information regarding medical evaluations, fit testing, and the respirator program. This information will facilitate employee involvement in the respirator program, assist the employer in auditing the adequacy of the program, and provide a record for compliance determinations by OSHA.

- Medical Evaluation – Records of medical evaluations required by this section must be retained and made available in accordance with section 3204.



- Fit Testing – CSUF shall establish a record of the quantitative fit tests administered to an employee including:
  - The name of the employee tested;
  - Type of fit test performed;
  - Specific make, model, style, and size of respirator tested;
  - Date of test; and
  - The pass/fail results and fit factor for QNFTs.
- Fit test records shall be retained for respirator users until the next fit test is administered.
- EHS shall retain a current copy of the respirator program.

Appendix A, Filter Cartridge Selection  
Appendix B, Voluntary Respirator Use

**Responsible Executive:** Vice President for Administration and Finance

**Responsible Office:** Environmental Health and Safety

**Originally Issued:** 6/1992

**Revised:** 2/1996, 5/2007, 5/2010, 2/2012, 6/2018, 4/2019, 4/2020, 2/2021, 1/2022

## Appendix A to CSUF Respiratory Protection Program

### Respirator Selection Chart

Job Categories	Type of Job Task	Mask	Filter
Art Technician	Spray painting operations	1	A
	General dusty condition (Voluntary)	5	N/A
	Welding operations in well ventilated areas (Non-stainless steel surface)	5	N/A
Auto Shop Mechanic	Asbestos brake change out operations	1	B
	General dusty or oily environment (Voluntary)	5, 6	N/A
	Welding operations in well ventilated areas (Non-stainless steel surface)	5	N/A
Building Service Engineer, Refrigeration Mechanic	General dusty or oily environment (Voluntary)	5, 6	N/A
	Work within fume hoods lab hood ductwork	1	C
	Sulfuric acid transfer	1	C
	Chlorine transfer	1	D
Chem/Bio/Physics Technicians	Welding operations in well ventilated areas (Non-stainless steel surface)	5	N/A
	General dusty environment (Voluntary)	5	N/A
	Work with formaldehyde	1, 2	E
Groundswoker, Tree Trimmers, Custodian, Animal Care Worker	General dusty environment (Voluntary)	5	N/A
Painter	Spray painting operations.	1	A
	General dusty or oily environment (Voluntary)	5, 6	N/A
Pesticide Applicator	Spraying liquid or gaseous pesticides in areas with limited ventilations.	1	A
Police Officer	General dusty environment (Voluntary)	5	N/A
	Emergency response	2	F
Building Maintenance, Carpenter, Electrician, Plumber, Skilled Labor	General dusty environment (Voluntary)	5	N/A
	Asbestos abatement (Authorized personnel)	1, 2, 3	B
	Under-sink trap at laboratories (DBH, MH, Etc.)	1	C
Theater Technician	Spray painting operations	1	A
	Welding operations in well ventilated areas (Non-stainless steel surface)	5	N/A
	General dusty condition (Voluntary)	5	N/A
SHCC Personnel	Aerosol Transmissible Disease Outbreak/Testing	5	N/A
EHS Response Team	Emergency response	1, 2, 4	G

#### Type of Mask

- 1 = Half Face
- 2 = Full Face
- 3 = Powered Air-Purifying Respirator
- 4 = Pressure Demand SCBA
- 5 = N-95, General Dust
- 6 = P-95 Dusty, Oily Environment

#### Type of Filter Cartridge

- A = Organic Vapor/P100 (Black/Magenta)
- B = P-100 or HEPA (Magenta)
- C = Organic Vapor / Acid Gas (Yellow)
- D = Chlorine (Orange)
- E = Formaldehyde (Olive)
- F = CBRN
- G = Multi-gas/Organic Vapor/P100 (Olive/Magenta)

## Appendix B to CSUF Respiratory Protection Program

### Voluntary Respirator Use

---

Respirators are an effective method of protection against designated hazards when properly selected and worn. Respirator use is encouraged even when exposures are below the exposure limit, to provide an additional level of comfort and protection for workers. However, if a respirator is used improperly or not kept clean, the respirator itself can become a hazard to the worker. Sometimes, workers may wear respirators to avoid exposures to hazards, even if the amount of hazardous substance does not exceed the limits set by OSHA standards. If your employer provides respirators for your voluntary use, or if you provide your own respirator, you need to take certain precautions to be sure that the respirator itself does not present a hazard.

You should do the following:

1. Read and heed all instructions provided by the manufacturer on use, maintenance, cleaning and care, and warnings regarding the respirator's limitations.
2. Choose respirators certified for use to protect against the contaminant of concern. NIOSH, the National Institute for Occupational Safety and Health of the U.S. Department of Health and Human Services, certifies respirators. A label or statement of certification should appear on the respirator or respirator packaging. It will tell you what the respirator is designed for and how much it will protect you.
3. Do not wear your respirator into atmospheres containing contaminants for which your respirator is not designated to protect against. For example, a respirator designed to filter dust particles will not protect you against gases, vapors or very small solid particles of fumes or smoke.
4. Keep track of your respirator so that you do not mistakenly use someone else's respirator.